

## INA 2 Taktol ST Plus

### General Description - Application

INA 2Taktol ST Plus is a high quality air-cooled two-stroke engine oil recommended for all types of chain saws, motorcycles and mopeds, as well as for many other types of equipment such as horticultural equipment, mowers, pumps and generators. It offers outstanding cleanliness, anticorrosion and anti-wear properties and provides very good protection against port blocking and spark plug fouling. It's low ash content and synthetic component provide low engine smoke and low exhaust pipe emission. Suitable for use in all types of gasolines in the mixing ratio defined by engine manufacturer.

### Performance Level - Specifications

API TC+  
 JASO FC  
 ISO L-EGC  
 INA N 22-103 TIP 3

Properties	INA 2Taktol ST Plus	Method
Appearance and Colour	clear, red oil	visual
Density at 15 °C, g/cm <sup>3</sup>	0,869	ASTM D 4052
Kinematic Viscosity, mm <sup>2</sup> /s - at 40 °C - at 100 °C	52 8,1	ISO 3104
Flash Point (COC), °C	110	ISO 2592
Pour Point, °C	-35	ISO 3016
Base Number, mgKOH/g	1,42	ISO 3771
Sulphated Ash, % mass	0,12	ISO 3987
Content of Water and Mechanical Impurities, vol. %	none	ISO 3734
Corrosion (Cu, 100 °C, 3 h)	1 a	ISO 2160

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.