

INA Ultra Garden 4T

General Description – Application

INA Ultra Garden 4T is high quality monograde motor oil for small gasoline and diesel four stroke engines. It's an ideal choice for high level reliable lubrication of four stroke engines of lawn mowers, lawnmower tractors, rotary hoes, cultivators, generators and other 4T engines, from spring to fall.

It offers reliable wear and corrosion protection and prevents deposit and varnish formation.

It complies with the engine oil regulations of Briggs & Stratton, Honda and other engine manufacturer. Oil change periods should follow the service manual specifications.

Performance Level - Specifications

API SJ/CF
CCMC G4/PD2
MIL-L-46152D
SAE J300 Apr13
INA N 22-126

Properties	INA Ultra Garden 4T	Method
SAE classification	SAE 30	
Appearance and Colour	clear, brown oil	visual
Density at 15°C, g/cm ³	0,893	ASTM D 4052
Kinematic Viscosity, mm ² /s - at 40 °C - at 100 °C	97,70 10,80	ISO 3104
Viscosity Index	95	ISO 2909
Flash Point (COC), °C	250	ISO 2592
Pour Point, °C	-21	ISO 3016
Base Number, mgKOH/g	7,4	ISO 3771
Corrosion (Cu, 100 °C, 3 h)	1 a	ISO 2160
Content of Water and Mechanical Impurities, vol. %	none	ISO 3734

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.